



# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 28/05/2015 Revision date: 14/06/2016 Supersedes: 06/11/2015 Version: 1.10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Name	: SP 106 Resin
Type of product	: Epoxy resin
Product group	: Resin

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category	: Industrial use
Industrial/Professional use spec	: For professional use only

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd  
St Cross Business Park  
PO30 5WU Isle of Wight - United Kingdom  
T +44 (0) 1983 828 000  
[contact@gurit.com](mailto:contact@gurit.com) - [www.gurit.com](http://www.gurit.com)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 2392 242148

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Sensitisation — Skin, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

GHS09

Signal word (CLP)

: Warning

Hazardous ingredients

: reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight  $\leq 700$ ); furfuryl alcohol

Hazard statements (CLP)

: H302 - Harmful if swallowed  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	H351 - Suspected of causing cancer
	H373 - May cause damage to organs through prolonged or repeated exposure
	H411 - Toxic to aquatic life with long lasting effects
	: P201 - Obtain special instructions before use
	P202 - Do not handle until all safety precautions have been read and understood
	P260 - Do not breathe vapours
	P264 - Wash hands, forearms and face thoroughly after handling
	P270 - Do not eat, drink or smoke when using this product
	P272 - Contaminated work clothing should not be allowed out of the workplace

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8 (REACH-no) 01-2119456619-26	$\geq$ 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
furfuryl alcohol	(CAS No) 98-00-0 (EC no) 202-626-1 (EC index no) 603-018-00-2 (REACH-no) 01-2119493965-18	10 - 25	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8 (REACH-no) 01-2119456619-26	(C $\geq$ 5) Eye Irrit. 2, H319 (C $\geq$ 5) Skin Irrit. 2, H315

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists, take medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Inhalation may cause irritation, cough, short breathing.
Symptoms/injuries after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.
Symptoms/injuries upon intravenous administration	: Not established.

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Other information : Collect contaminated fire fighting water separately. It must not enter drains.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Maximum storage period : 2 year

Storage temperature : ≤ 30 °C

Storage area : Store away from heat. Store in a well-ventilated place.

Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Protective clothing. Safety glasses.

Hand protection:

Wear protective gloves. Protective gloves

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. In case of inadequate ventilation wear respiratory protection



Environmental exposure controls : Avoid release to the environment.

Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: clear.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not Applicable Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.164 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1360 cP 20°C
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

ATE CLP (oral)	800.000 mg/kg bodyweight
----------------	--------------------------

#### reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LD50 oral rat	11400 mg/kg
---------------	-------------

#### furfuryl alcohol (98-00-0)

LD50 oral rat	110 mg/kg
LD50 dermal rabbit	657 mg/kg
LC50 inhalation rat (ppm)	233 ppm/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

#### SP 106 RESIN

Viscosity, kinematic	1168.38487973 mm <sup>2</sup> /s
----------------------	----------------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

#### reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LC50 fish 1	1.5 mg/l
LC50 fish 2	2 mg/l

#### furfuryl alcohol (98-00-0)

LC50 fish 1	32 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
-------------	---

### 12.2. Persistence and degradability

#### reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
<b>14.1. UN number</b> 3082	3082	3082
<b>14.2. UN proper shipping name</b> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
<b>Transport document description</b> UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III, (E)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b> 9	9	9
		
<b>14.4. Packing group</b> III	III	III
<b>14.5. Environmental hazards</b> Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available		

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 601, 375
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special provisions for carriage - Packages (ADR) : V12  
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV13  
 Hazard identification number (Kemler No.) : 90  
 Orange plates :



Tunnel restriction code (ADR) : E  
 EAC code : •3Z

### - Transport by sea

Special provisions (IMDG) : 274, 335  
 Limited quantities (IMDG) : 5 L  
 Excepted quantities (IMDG) : E1  
 Packing instructions (IMDG) : P001, LP01  
 Special packing provisions (IMDG) : PP1  
 IBC packing instructions (IMDG) : IBC03  
 Tank instructions (IMDG) : T4  
 Tank special provisions (IMDG) : TP2, TP29  
 EmS-No. (Fire) : F-A  
 EmS-No. (Spillage) : S-F  
 Stowage category (IMDG) : A

### - Air transport

PCA Excepted quantities (IATA) : E1  
 PCA Limited quantities (IATA) : Y964  
 PCA limited quantity max net quantity (IATA) : 30kgG  
 PCA packing instructions (IATA) : 964  
 PCA max net quantity (IATA) : 450L  
 CAO packing instructions (IATA) : 964  
 CAO max net quantity (IATA) : 450L  
 Special provisions (IATA) : A97, A158, A197  
 ERG code (IATA) : 9L

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
 Contains no substance on the REACH candidate list  
 Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Carc. 2	Carcinogenicity, Category 2

# SP 106 Resin

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*



# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 28/05/2015 Revision date: 15/06/2016 Supersedes: 31/03/2016 Version: 2.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Name	: SP 106 Slow Hardener
Type of product	: Hardener (Crosslinker)
Product group	: Hardener

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category	: Industrial use
Industrial/Professional use spec	: For professional use only

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd  
St Cross Business Park  
PO30 5WU Isle of Wight - United Kingdom  
T +44 (0) 1983 828 000  
[contact@gurit.com](mailto:contact@gurit.com) - [www.gurit.com](http://www.gurit.com)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 2392 242148

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal), Category 4	H312
Skin corrosion/irritation, Category 1B	H314
Sensitisation — Skin, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Reproductive toxicity, Category 2	H361
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. Harmful in contact with skin. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: Phenol; 3,6-diazaoctanethylenediamin, triethylenetetramine; Propylene glycol diamine, 2-amino-, diether with Propylene; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 2,2'-iminodiethylamine, diethylenetriamine; bisphenol A, 4,4'-isopropylidenediphenol

Hazard statements (CLP)

: H302+H312 - Harmful if swallowed or in contact with skin  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H341 - Suspected of causing genetic defects

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	H361 - Suspected of damaging fertility H412 - Harmful to aquatic life with long lasting effects P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P260 - Do not breathe vapours P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product P272 - Contaminated work clothing should not be allowed out of the workplace
--------------------------------	--

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	(CAS No) 2855-13-2 (EC no) 220-666-8 (EC index no) 612-067-00-9 (REACH-no) 01-2119514687-32	>= 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
2,2'-iminodiethylamine, diethylenetriamine	(CAS No) 111-40-0 (EC no) 203-865-4 (EC index no) 612-058-00-X (REACH-no) 01-2119473793-27	10 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H336
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS No) 9046-10-0 (EC no) 618-561-0 (REACH-no) 01-2119557899-12	10 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
bisphenol A, 4,4'-isopropylidenediphenol	(CAS No) 80-05-7 (EC no) 201-245-8 (EC index no) 604-030-00-0 (REACH-no) 01-9119457856-23	5 - 10	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361f STOT SE 3, H335 Aquatic Chronic 2, H411
3,6-diazaoctanethylenediamin, triethylenetetramine	(CAS No) 112-24-3 (EC no) 203-950-6 (EC index no) 612-059-00-5 (REACH-no) 01-2119487919-13	1 - 5	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Phenol	(CAS No) 108-95-2 (EC no) 203-632-7 (EC index no) 604-001-00-2 (REACH-no) 01-2119471329-32	1 - 3	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1B, H314 Muta. 2, H341 STOT RE 2, H373

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Phenol	(CAS No) 108-95-2 (EC no) 203-632-7 (EC index no) 604-001-00-2 (REACH-no) 01-2119471329-32	( 1 =<C < 3) Skin Irrit. 2, H315 ( 1 =<C < 3) Eye Irrit. 2, H319 (C >= 3) Skin Corr. 1B, H314

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Serious damage to eyes.
Symptoms/injuries after ingestion	: Burns.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Protective clothing.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin, eyes and clothing. Do not breathe dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 30 °C
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Phenol (108-95-2)		
EU	IOELV TWA (mg/m <sup>3</sup> )	8 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	2 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	16 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	4 ppm
United Kingdom	Local name	Phenol
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	7.8 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	2 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	16 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	4 ppm
United Kingdom	Remark (WEL)	Sk
2,2'-iminodiethylamine, diethylenetriamine (111-40-0)		
United Kingdom	Local name	2,2'-Iminodi(ethylamine)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	4.3 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	12.9 mg/m <sup>3</sup> (calculated)
United Kingdom	WEL STEL (ppm)	3 ppm (calculated)
United Kingdom	Remark (WEL)	Sk
bisphenol A, 4,4'-isopropylidenediphenol (80-05-7)		
EU	Local name	Bisphenol A (inhalable dust)
EU	IOELV TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable dust)
United Kingdom	Local name	Bisphenol A : inhalable dust
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable dust)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	30 mg/m <sup>3</sup> (inhalable dust)

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Protective clothing. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended



Environmental exposure controls : Avoid release to the environment.

Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: Amine-like.
Odour threshold	: No data available

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.968 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 106 cP
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin.

ATE CLP (oral)	995.067 mg/kg bodyweight
ATE CLP (dermal)	1086.760 mg/kg bodyweight

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LD50 oral rat	1030 mg/kg
---------------	------------

#### Phenol (108-95-2)

LD50 oral rat	340 mg/kg
LD50 dermal rabbit	630 mg/kg

#### 3,6-diazaoctanethylenediamin, triethylenetetramine (112-24-3)

LD50 oral rat	2500 mg/kg
LD50 dermal rabbit	550 mg/kg

#### Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)

LD50 oral rat	1100 mg/kg
LD50 dermal rabbit	1555 mg/kg

#### 2,2'-iminodiethylamine, diethylenetriamine (111-40-0)

LD50 oral rat	1080 mg/kg
---------------	------------

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>2,2'-iminodiethylamine, diethylenetriamine (111-40-0)</b>	
LD50 dermal rabbit	672 mg/kg
<b>bisphenol A, 4,4'-isopropylidenediphenol (80-05-7)</b>	
LD50 oral rat	3300 mg/kg
LD50 dermal rabbit	3 ml/kg
LC50 inhalation rat (mg/l)	> 0.17 mg/l (Exposure time: 6 h)
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Serious eye damage, category 1, implicit
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility.
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
<b>SP 106 SLOWHARDENER</b>	
Viscosity, kinematic	109.50413223 mm <sup>2</sup> /s

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

<b>3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)</b>	
EC50 Daphnia 1	14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])
EC50 72h algae (1)	37 mg/l (Species: Desmodesmus subspicatus)
<b>Phenol (108-95-2)</b>	
LC50 fish 1	11.9 - 50.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	20.5 - 25.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	4.24 - 10.7 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Daphnia 2	10.2 - 15.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h algae (1)	187 - 279 mg/l (Species: Desmodesmus subspicatus [static])
EC50 96h algae (1)	46.42 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h algae (2)	0.0188 - 0.1044 mg/l (Species: Pseudokirchneriella subcapitata [static])
<b>3,6-diazaoctanethylenediamin, triethylenetetramine (112-24-3)</b>	
LC50 fish 1	570 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
LC50 fish 2	495 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	31.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h algae (1)	2.5 mg/l (Species: Desmodesmus subspicatus)
EC50 72h algae (2)	20 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h algae (1)	3.7 mg/l (Species: Pseudokirchneriella subcapitata)
<b>2,2'-iminodiethylamine, diethylenetriamine (111-40-0)</b>	
LC50 fish 1	248 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
LC50 fish 2	1014 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 Daphnia 1	16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h algae (1)	1164 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h algae (1)	345.6 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h algae (2)	592 mg/l (Species: Desmodesmus subspicatus)
<b>bisphenol A, 4,4'-isopropylidenediphenol (80-05-7)</b>	
LC50 fish 1	3.6 - 5.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	4.0 - 5.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	10.2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h algae (1)	2.5 mg/l (Species: Pseudokirchneriella subcapitata)

### 12.2. Persistence and degradability

No additional information available

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.3. Bioaccumulative potential

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Log Pow	0.79 (at 23 °C)
---------	-----------------

#### Phenol (108-95-2)

BCF fish 1	(no significant bioaccumulation)
------------	----------------------------------

Log Pow	1.47
---------	------

#### 3,6-diazaoctanethylenediamin, triethylenetetramine (112-24-3)

BCF fish 1	(no bioaccumulation expected)
------------	-------------------------------

Log Pow	-1.4
---------	------

#### 2,2'-iminodiethylamine, diethylenetriamine (111-40-0)

BCF fish 1	0.3 - 1.7
------------	-----------

Log Pow	-1.3
---------	------

#### bisphenol A, 4,4'-isopropylidenediphenol (80-05-7)

BCF fish 1	5.1 - 13.8
------------	------------

Log Pow	2.2
---------	-----

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
<b>14.1. UN number</b>		
2735	2735	2735
<b>14.2. UN proper shipping name</b>		
POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 2,2'-iminodiethylamine, diethylenetriamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 2,2'-iminodiethylamine, diethylenetriamine)	Polyamines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 2,2'-iminodiethylamine, diethylenetriamine)
<b>Transport document description</b>		
UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 2,2'-iminodiethylamine, diethylenetriamine), 8, II, (E)	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 2,2'-iminodiethylamine, diethylenetriamine), 8, II	UN 2735 Polyamines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 2,2'-iminodiethylamine, diethylenetriamine), 8, II
<b>14.3. Transport hazard class(es)</b>		
8	8	8
		
<b>14.4. Packing group</b>		
II	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA
No supplementary information available		

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: C7
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

#### - Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP27
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

#### - Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3
ERG code (IATA)	: 8L

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

# SP 106 Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H361	Suspected of damaging fertility or the unborn child
H361f	Suspected of damaging fertility
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
Acute Tox. 4 (Dermal)	H312	Calculation method
Skin Corr. 1B	H314	Calculation method
Skin Sens. 1	H317	Calculation method
Muta. 2	H341	Calculation method
Repr. 2	H361	Calculation method
Aquatic Chronic 3	H412	Calculation method

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*