

POLYVINE.



Gold Size water based

DÉCOR WOOD STAIN

PRODUCT

ACRYLIC SIZE

DESCRIPTION

An Acrylic adhesive with an extended open time for bonding metal leaf to a variety of surfaces.

APPLICATION

Seal porous surfaces

Ensure Acrylic size is well mixed. Ensure all surfaces are clean and free from grease, oil, dirt and contaminants. Apply 1 coat using a good quality brush. Leave until the coating turns clear, minimum of 15 minutes.

Apply the metal leaf

USES

Furniture. Woodwork. Plaster work. Non Ferrous metals.

COVERAGE

Approx. 15 sq. m per litre 160 sq. ft per US qt

SHEEN LEVEL N/A

CONTAINERS

500ml, 1L, 1 US Pint, US Quart.

No OF COATS 1 coat

DRYING TIME

15mins-1 hr, depending on temperature

RECOAT TIME N/A

CURING

Does not dry, remains tacky.

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

FLAMMABILITY No fire hazard before or during use, or in the cured state.

TECHNICAL DATA SHEET

POLYVINE.

Gold Size water based**DÉCOR WOOD STAIN**

TECHNICAL DATA SHEET

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Further information may be obtained from:

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to access the suitability of the product on a test area before application

POLYVINE LIMITED

Vine House
Cheddar Business Park
Wedmore Rd.
Cheddar BS27 3EB
United Kingdom

Telephone No. 0845 017 1671
International +44 845 017 1671
Fax: 0845 017 1672
Email info@polyvine.co.uk

www.polyvine.com

POLYVINE.

September
2015