

SDS Report

No. HKHC1508005846HC

Date : Sep 10, 2015 Page 1 of 1

ANTARI LIGHTING & EFFECTS LTD
NO.8, LN. 231, SEC. 1,NANKAN RD.,LUZHU TOWNSHIP,TAOYUAN COUNTY,338,Taiwan

Job No. : HKHC150800002612

The following sample was submitted and identified by the client as

Product Description : MG-550 Magican
SGS Sample No. : HKHC150800002612 -101
Sample Receiving Date : Aug 21 – Sep 09, 2015
Testing Period : Sep 09 – Sep 10, 2015

Service Requested : Preparation of Safety Data Sheet (SDS) for the sample with submitted information.

Summary : As per request, the contents and formats of the SDS are prepared in accordance with European Commission Regulation (EC) No 1907/2006, Regulation (EC) No 1272/2008 and Regulation (EU) No 2015/830, and is provided per attached.

Signed for and on behalf of

SGS Hong Kong Ltd.



HO CHI MING, RICKY
SENIOR MANAGER - COSMETICS, PERSONAL CARE & HOUSEHOLD SERVICES

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



	SAFETY DATA SHEET	Page : 1 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name/designation : MG-550 Magican
 Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
 Main use category : Industrial use, Professional use, Consumer use

1.2.2. Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Antari Lighting and Effects Ltd.
 No.8, Ln. 231, Sec. 1, Nankan Rd.,
 Luzhu Township, Taoyuan County 338 - Taiwan (R.O.C.)
 T +886 33225829
jasonho@antari.com.tw

1.4. Emergency telephone number

Emergency number : +88633225829
 Only available during office hours.

Country	Official advisory body	Address	Emergency number
IRELAND (REPUBLIC OF)	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	+353 18 37 99 64/+353 1 809 21 66
UNITED KINGDOM	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229

Full text of H-statements: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms :



GHS02

Signal word : Danger
 Hazard statements : H222 - Extremely flammable aerosol.
 H229 - Pressurised container: May burst if heated.
 Precautionary statements : P102 - Keep out of reach of children.

	SAFETY DATA SHEET	Page : 2 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

Other hazards : Vapours can form explosive mixtures with air. Results of PBT and vPvB assessment : Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Comments : Aerosol

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane	(CAS No.) 106-97-8 (EC No) 203-448-7 (EC Index) 601-004-00-0	50 - 70	Flam. Gas 1, H220 Liquefied gas, H280
Propane	(CAS No.) 74-98-6 (EC No) 200-827-9 (EC Index) 601-003-00-5	20 - 30	Flam. Gas 1, H220 Liquefied gas, H280
White mineral oil (petroleum)	(CAS No.) 8042-47-5 (EC No) 232-455-8 (EC Index) -	10 - 20	Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person or a person with cramps. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance. Treat symptomatically.

Inhalation : Remove person to fresh air and keep comfortable for breathing. In case of doubt or persistent symptoms, consult always a physician.

Skin contact : Take off contaminated clothing. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.

Eye contact : Rinse immediately carefully and thoroughly with eye-bath or water. In case of doubt or persistent symptoms, consult always a physician.

In case of ingestion : Rinse mouth thoroughly with water. Do not induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : High concentration of vapours may induce: headache, nausea, dizziness.

Skin contact : Health injuries are not known or expected under normal use.

Eye contact : Health injuries are not known or expected under normal use.

Ingestion : Ingestion is not considered a potential route of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

	SAFETY DATA SHEET	Page : 3 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO₂), powder, alcohol-resistant foam, hazy water.
 Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Extremely flammable aerosol. Risk of ignition. Vapours are heavier than air and may spread along floors. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. Aerosol cans may rupture and become projectiles. In use, may form flammable/explosive vapour-air mixture. Do not spray on naked flames or any incandescent material. The pressure in sealed containers can increase under the influence of heat.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂).

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.

Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Do not breathe aerosol. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately grounded. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Leave to vaporize. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Disposal: see section 13.

	SAFETY DATA SHEET	Page : 4 / 14
		Revision nr : 1.0
	MG-550 Magican	Issue date : 09/09/2015
		Supersedes :

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Do not breathe aerosol. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Remove all sources of ignition. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Hygiene measures : Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Extremely flammable aerosol. Store in a dry, cool and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Packaging materials : Keep only in the original container.

7.3. Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)		
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	800 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³
Austria	MAK Short time value (ppm)	1600 ppm
Belgium	Limit value (ppm)	1000 ppm (gas)
Bulgaria	OEL TWA (mg/m ³)	1900 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	1450 mg/m ³ 22 mg/m ³ (containing >=0.1% 1,3-Butadiene)
Croatia	GVI (granična vrijednost izloženosti) (ppm)	600 ppm 10 ppm (containing >=0.1% 1,3-Butadiene)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	1810 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	750 ppm
Denmark	Grænseværdie (langvarig) (mg/m ³)	1200 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Estonia	OEL TWA (mg/m ³)	1500 mg/m ³
Estonia	OEL TWA (ppm)	800 ppm
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min) (ppm)	1000 ppm
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	800 ppm

	SAFETY DATA SHEET	Page : 5 / 14
		Revision nr : 1.0
	MG-550 Magican	Issue date : 09/09/2015
		Supersedes :

butane (106-97-8)		
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	2400 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Greece	OEL TWA (mg/m ³)	2350 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Hungary	AK-érték	2350 mg/m ³
Hungary	CK-érték	9400 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	3000 ppm (calculated)
Latvia	OEL TWA (mg/m ³)	300 mg/m ³
Poland	NDS (mg/m ³)	1900 mg/m ³
Poland	NDSch (mg/m ³)	3000 mg/m ³
Slovenia	OEL TWA (mg/m ³)	2400 mg/m ³ (containing >= 0.1 % Butadiene (203-450-8))
Slovenia	OEL TWA (ppm)	1000 ppm (containing >= 0.1 % Butadiene (203-450-8))
Slovenia	OEL STEL (mg/m ³)	9600 mg/m ³ (containing >= 0.1% Butadiene)
Slovenia	OEL STEL (ppm)	4000 ppm (containing >= 0.1% Butadiene)
Spain	VLA-ED (ppm)	1000 ppm
United Kingdom	WEL TWA (mg/m ³)	1450 mg/m ³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m ³)	1810 mg/m ³
United Kingdom	WEL STEL (ppm)	750 ppm
Norway	Grenseverdier (AN) (mg/m ³)	600 mg/m ³
Norway	Grenseverdier (AN) (ppm)	250 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	600 mg/m ³
Norway	Grenseverdier (Korttidsverdi) (ppm)	250 ppm
Switzerland	VME (mg/m ³)	1900 mg/m ³
Switzerland	VME (ppm)	800 ppm
Switzerland	VLE (mg/m ³)	7200 mg/m ³
Switzerland	VLE (ppm)	3200 ppm
Australia	TWA (mg/m ³)	1900 mg/m ³
Australia	TWA (ppm)	800 ppm
Canada (Quebec)	VEMP (mg/m ³)	1900 mg/m ³
Canada (Quebec)	VEMP (ppm)	800 ppm
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Propane (74-98-6)		
Austria	MAK (mg/m ³)	1800 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3600 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Limit value (ppm)	1000 ppm (gas)
Bulgaria	OEL TWA (mg/m ³)	1800,0 mg/m ³

	SAFETY DATA SHEET	Page : 6 / 14
		Revision nr : 1.0
	MG-550 Magican	Issue date : 09/09/2015
		Supersedes :

Propane (74-98-6)		
Denmark	Grænseværdie (langvarig) (mg/m ³)	1800 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Estonia	OEL TWA (mg/m ³)	1800 mg/m ³
Estonia	OEL TWA (ppm)	1000 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2000 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1100 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1800 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Greece	OEL TWA (mg/m ³)	1800 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	3000 ppm (calculated)
Poland	NDS (mg/m ³)	1800 mg/m ³
Portugal	OEL TWA (ppm)	1000 ppm
Romania	OEL TWA (mg/m ³)	1400 mg/m ³
Romania	OEL TWA (ppm)	778 ppm
Romania	OEL STEL (mg/m ³)	1800 mg/m ³
Romania	OEL STEL (ppm)	1000 ppm
Slovenia	OEL TWA (mg/m ³)	1800 mg/m ³
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m ³)	7200 mg/m ³
Slovenia	OEL STEL (ppm)	4000 ppm
Spain	VLA-ED (ppm)	1000 ppm
Norway	Grenseverdier (AN) (mg/m ³)	900 mg/m ³
Norway	Grenseverdier (AN) (ppm)	500 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	900 mg/m ³
Norway	Grenseverdier (Korttidsverdi) (ppm)	500 ppm
Switzerland	VME (mg/m ³)	1800 mg/m ³
Switzerland	VME (ppm)	1000 ppm
Switzerland	VLE (mg/m ³)	7200 mg/m ³
Switzerland	VLE (ppm)	4000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1800 mg/m ³
Canada (Quebec)	VEMP (ppm)	1000 ppm
USA - IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

	SAFETY DATA SHEET	Page : 7 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

Additional information	: Personal air monitoring :. Room air monitoring. Recommended monitoring procedures
8.2. Exposure controls	
Engineering control measures	: Provide adequate ventilation. Organisational measures to prevent /limit releases, dispersion and exposure. Safe handling: see section 7 . Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges.
Personal protection equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Repeated or prolonged exposure: Wear chemically resistant gloves (tested to EN374) . Suitable material: NBR (Nitrile rubber) BTT: >8h, >0,3mm). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection. (EN166): Safety glasses
Body protection	: Wear suitable protective clothing.
Respiratory protection	: Not required for normal conditions of use. In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (EN 140). Full face mask (EN 136). Filter type: AX/P (EN 141). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: Aerosol.
Colour	: Transparent.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point/freezing point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapour pressure	: No data available
Vapour density	: No data available
Relative density	: No data available
Solubility	: Water: No data available
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: No data available
Dynamic viscosity	: No data available

	SAFETY DATA SHEET	Page : 8 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Will ignite if exposed to intensive heat and air. Risk of explosion by shock, friction, fire or other sources of ignition. No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid temperatures above 50 °C. Safe handling: see section 7.

10.5. Incompatible materials

Oxidising substances. Safe handling: see section 7.

10.6. Hazardous decomposition products

Reference to other sections: 5.2.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

butane (106-97-8)	
LC50/inhalation/4h/rat	658 g/m ³ (Exposure time: 4 h)
Propane (74-98-6)	
LC50/inhalation/4h/rat	658 mg/l/4h
White mineral oil (petroleum) (8042-47-5)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rat	> 2000 mg/kg
LC50/inhalation/4h/rat	> 5 mg/l

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: No data available
Serious eye damage/eye irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met.)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met.)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met.)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met.)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met.)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met.)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met.)

	SAFETY DATA SHEET	Page : 9 / 14
		Revision nr : 1.0
	MG-550 Magican	Issue date : 09/09/2015
		Supersedes :

MG-550 Magican	
Vaporizer	Aerosol

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

White mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	> 100 mg/l (WAF)

12.2. Persistence and degradability

MG-550 Magican	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

MG-550 Magican	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No data available.
butane (106-97-8)	
Partition coefficient n-octanol/water	2,89
Propane (74-98-6)	
Partition coefficient n-octanol/water	2,3
White mineral oil (petroleum) (8042-47-5)	
Partition coefficient n-octanol/water	> 6

12.4. Mobility in soil

MG-550 Magican	
Mobility in soil	No data available

12.5. Results of PBT and vPvB assessment

MG-550 Magican	
Results of PBT assessment	No data available

12.6. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Avoid release to the environment. Dispose of empty containers and wastes safely. Safe handling: see section 7. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Packaging contaminated by the product : Do not pierce or burn, even after use. Never use pressure to empty container.

List of proposed waste codes/waste designations in accordance with EWC (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

	SAFETY DATA SHEET	Page : 10 / 14
		Revision nr : 1.0
	MG-550 Magican	Issue date : 09/09/2015
		Supersedes :

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1950	1950	1950	1950	1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1			
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : 5F
 Special Provisions : 190, 327, 344, 625
 Limited quantities (ADR) : 1I
 Excepted quantities (ADR) : E0
 Packing instructions (ADR) : P207, LP02
 Special packing provisions (ADR) : PP87, RR6, L2
 Mixed packing provisions (ADR) : MP9
 Transport category (ADR) : 2
 Special provisions for carriage - Packages (ADR) : V14
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12
 Special provisions for carriage - Operation (ADR) : S2
 tunnel restriction code : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959
 Limited quantities (IMDG) : SP277
 Excepted quantities (IMDG) : E0
 Packing instructions (IMDG) : P207, LP02
 Special packing provisions (IMDG) : PP87, L2

	SAFETY DATA SHEET	Page : 11 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

EmS-No. (Fire) : F-D
 EmS-No. (Spillage) : S-U
 Stowage category (IMDG) : None
 Stowage and segregation (IMDG) : Protected from sources of heat For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.

- Air transport

PCA Excepted quantities (IATA) : E0
 PCA Limited quantities (IATA) : Y203
 PCA limited quantity max net quantity (IATA) : 30kgG
 PCA packing instructions (IATA) : 203
 PCA max net quantity (IATA) : 75kg
 CAO packing instructions (IATA) : 203
 CAO max net quantity (IATA) : 150kg
 Special provisions (IATA) : A145, A167, A802
 ERG code (IATA) : 10L

- Inland waterway transport

Classification code (ADN) : 5F
 Special provisions (ADN) : 19, 327, 344, 625
 Limited quantities (ADN) : 1 L
 Excepted quantities (ADN) : E0
 Equipment required (ADN) : PP, EX, A
 Ventilation (ADN) : VE01, VE04
 Number of blue cones/lights (ADN) : 1
 Carriage prohibited (ADN) : No
 Not subject to ADN : No

- Rail transport

Classification code (RID) : 5F
 Special provisions (RID) : 190, 327, 344, 625
 Limited quantities (RID) : 1L
 Excepted quantities (RID) : E0
 Packing instructions (RID) : P207, LP02
 Special packing provisions (RID) : PP87, RR6, L2
 Mixed packing provisions (RID) : MP9
 Transport category (RID) : 2
 Special provisions for carriage – Packages (RID) : W14
 Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12
 Colis express (express parcels) (RID) : CE2
 Hazard identification number (RID) : 23
 Carriage prohibited (RID) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Code: IBC : No data available.

	SAFETY DATA SHEET	Page : 12 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	White mineral oil (petroleum)
3.a. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	MG-550 Magican - butane - Propane
3.b. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	White mineral oil (petroleum)
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	butane - Propane

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : White mineral oil (petroleum) is listed

SZW-lijst van mutagene stoffen : White mineral oil (petroleum) is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out

SECTION 16: Other information

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
--	--------------------------------------

	SAFETY DATA SHEET	Page : 13 / 14
		Revision nr : 1.0
	MG-550 Magican	Issue date : 09/09/2015
		Supersedes :

	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Code LEL = Lower Explosive Limit/Lower Explosion Limit UEL = Upper Explosion Limit/Upper Explosive Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet : European Chemicals Agency, INCHEM, LOLI.

Full text of H- and EUH-statements:

Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, hazard category 1
Liquefied gas	Gases under pressure : Liquefied gas
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container. May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.

	SAFETY DATA SHEET	Page : 14 / 14
		Revision nr : 1.0
		Issue date : 09/09/2015
	MG-550 Magican	Supersedes :

and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.