Super Bravo B/C

- · Hardwearing, heterogenous reversible sheet flooring
- Colors Black/Black, Grey/Grey, Black/White, and B;ack/Grey

SPECIFICATION









2m x up to 30m 6.56ft x up to 98ft



2.17kg/m2 4lbs/yd2



GENERAL PERFORMANCE

EN 651









ACOUSTIC IMPACT SOUND REDUCTION

ISO 717-2

10dB



SLIP RESISTANCE

AS/NZS 4856 DIN 51130 R9



REACTION TO FIRE

EN 13501-1 Class Cfl-s1



RESISTANCE TO CHEMICALS

EN 423 (ASTM F 1303-99) Excellent chemical resistance



LIGHT FASTNESS

EN 20105-B02 (Method 3) ≥6



ABRASION RESISTANCE

EN 649 Group T



INDENTATION - RESIDUAL

EN 433 < 0.2mm



DIMENSIONAL STABILITY

EN 434 0.2



FLEXIBILITY

EN 435 (Method A) Pass



VOC EMISSIONS

No Solvents USed



THERMAL CONDUCTIVITY

N/A



Contains antimicrobial agents for improved hygiene protection. This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)

EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.



APPLICATIONS

Ballet, Modern, Jazz, Call for percussive use



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance,

call 800-523-0960



Stagestep Inc. 4701 Bath St # 46, Philadelphia Pa 19137 215-636-9000, 800-523-0960

SUPER BRAVO B/C

HETEROGENOUS

PERFORMANCE AND

PROPERTIES

October 2007